



LAP Enterprise Co.,Ltd.

48/98 Moo 2, Bang Rak Yai, Bang Bua Thong, Nonthaburi 11110

Tel. 093 963 6364 Fax. 02 000 6261 e-mail : iyasilicone@yahoo.com www.iyasilicone.net

iya Liquid Nail (Oil Base)

iya Liquid Nail (Oil Base) is made of silicone rubber synthetic rubber, with high content and high viscosity, low liquidity, alternative to conventional nails, screws, grill-free nail.

TECHNICAL DATA :

Appearance	Ointment
Solid Content	Over 70%
Primary Open Time	5 minutes
Over Drying Time	48 hours
Specific Gravity	1.10±0.1 kg/cm ³
Adhesive Strength	10 kg/cm
Operate Time	2-5 minutes
Flash Point	0°C

FEATURES :

- Strong bonding strength-which copes with shrinkage and thermal movement
- Easily extruded and easy to use in low temperatures
- Paintable when dry, to offer you a neat, quality finished job
- Doesn't drip, sag or string, so there is less mess during the application
- Bridges gaps on rough and ill fitting construction material
- Not for use on polyethylene, polypropylene, Teflon, silicone or polystyrene

USES :

- This applies to adhesion between materials
- Wood to wood assembly
- Metal joints to timber
- Lumber and treated lumber
- Thresholds; prefinished panel
- Bathroom fixtures
- Fiberglass shower enclosures
- Metal, brick, plaster, masonry, concrete, drywall, ceramic tile, plywood, particle board

APPLICATION :

- All the surfaces must be dry, no oil, grease and dust
- Cut end off nipple to open and fit nozzle cut to required opening
- Apply using a cartridge gun. Apply a 'zig zag' bead of adhesive along the joints. Stud or batten
- Assemble joint within 10 minutes using nails, screws or clamping sufficient to give contact over the whole area
- Allow adhesive to set (at least 24 hours) before removing clamps temporary fasteners
- Warm and prompt
- Tube did not run out of the plastic can be used the next time, after taking away mouth of glue, can be used the same effect

SHELF LIFE :

- 24 months when properly stored
- Store in cool, dry, dark place
- Keep out of reach of children